Serial No.:

10/066,738

Inventor(s):

Ramesh Keshavaraj

U.S. PTO Customer No. 25280

Case No.: 2102REI

IN THE CLAIMS

1. (Currently Amended) An airbag fabric for incorporation within an airbag cushion comprising a woven fabric substrate, at least a portion of which is adhered to a film coated or laminated, wherein said woven fabric substrate has a cover factor below about 1900 1600, and is made from yarns from about 100 to about 630 denier, and wherein the air permeability of said airbag fabric is less than about 0.5 cfm under 124 Pa pressure at about 25° C.

- 2. (Currently Amended) The airbag fabric of claim 1 wherein said woven fabric substrate is adhered to a film comprising materials coated or laminated with a coating or film selected from the group consisting of polyurethane, polyacrylate, polyamide, polyester, and copolymers thereof.
- 3-5 (Cancel)
- 6. (Original) The airbag fabric of claim 5 wherein said coating or laminate comprises polyurethane.
- 7. (Original) The airbag fabric of claim 6 wherein the thickness of said coating or laminate is from 0.1 to about 3.5 mils.
- 8. (Original) An airbag cushion comprising the airbag fabric of claim 6.
- (Original) An airbag cushion comprising the airbag fabric of claim 7.
- 10. (Currently Amended) The airbag fabric of claim 4 <u>1</u> wherein said film <u>coating or laminate</u> comprises polyurethane.
- 11. (Currently Amended) The airbag fabric of claim 10 wherein the thickness of said film coating or laminate is from 0.1 0.4 to about 3.5 mils.
- 12. (Original) An airbag cushion comprising the airbag fabric of claim 11.
- 13. (Original) An airbag cushion comprising the airbag fabric of claim 10.

Serial No.:

10/066,738

Inventor(s):

Ramesh Keshavaraj

U.S. PTO Customer No. 25280

Case No.: 2102REI

14. (Currently Amended) The airbag fabric of claim 3 wherein said film-coating or laminate comprises polyurethane.

- 15. (Currently Amended) The airbag fabric of claim 14 wherein the thickness of said film coating or laminate is from 0.1 to about 3.5 mils.
- 16. (Original) An airbag cushion comprising the airbag fabric of claim 15.
- 17. (Original) An airbag cushion comprising the airbag fabric of claim 14.
- 18. (Currently Amended) The airbag fabric of claim 1 wherein the thickness of said film coating or laminate is from 0.1 to about 3.5 mils.
- 19. (Original) An airbag cushion comprising the airbag fabric of claim 18.
- 20. (Original) An airbag cushion comprising the airbag fabric of claim 1.
- 21. (Currently Amended) An airbag fabric for incorporation within an airbag cushion comprising a woven fabric substrate, at least a portion of which is coated <u>or laminated</u> with materials selected from the group consisting of polyurethane, polyacrylate, polyamide, polyester, and copolymers thereof, wherein said woven fabric substrate has a cover factor below about 1900 1600, and comprises yarns from about 100 to about 630 denier, and wherein the air permeability of said airbag fabric is less than about 0.5 cfm under 124 Pa pressure at about 25° C.

22-24 (Cancel)

25. (Currently Amended) The airbag fabric of Claim 22 21 wherein said coating comprises polyurethane.

26-27 (Cancel)

28. (Previously Presented) The airbag fabric of Claim 21 wherein the thickness of said coating is from 0.1 to about 3.5 mils.

Serial No.:

10/066,738

Inventor(s):

Ramesh Keshavaraj

U.S. PTO Customer No. 25280

Case No.: 2102REI

29. (Previously Presented) The airbag fabric of Claim 25 wherein the thickness of said coating is from 0.1 to about 3.5 mils.

30-31 (Cancel)

- 32. (Previously Presented) An airbag cushion comprising the airbag fabric of Claim 21.
- 33. (Previously Presented) An airbag cushion comprising the airbag fabric of Claim 25.
- 34-35 (Cancel)
- 36. (Previously Presented) An airbag cushion comprising the airbag fabric of Claim 28.
- 37. (Previously Presented) An airbag cushion comprising the airbag fabric of Claim 29.
- 38-39 (Cancel)
- 40. (Currently Amended) An airbag fabric for incorporation within an airbag cushion comprising a woven fabric substrate, at least a portion of which is coated or adhered to a film laminated, wherein said woven fabric has a cover factor below about 1775 1600 and fibers having deniers equal to or less than 525, and wherein the air permeability of said airbag fabric is less than about 0.5 cfm under 124 Pa pressure at about 25° C.
- 41. (Previously Presented) The airbag fabric of claim 40 wherein said woven fabric substrate is adhered to a film comprising materials selected from the group consisting of polyurethane, polyacrylate, polyamide, polyester, and copolymers thereof.
- 42. (Previously Presented) The airbag fabric of Claim 40 wherein said woven fabric has a cover factor below about 1750 and fibers having deniers equal to or less than 420.
- 43. (Previously Presented) The airbag fabric of Claim 42 wherein said woven fabric has a cover factor below about 1750 and fibers having deniers equal to or less than 420.

Serial No.: 10/06

10/066,738

Inventor(s):

Ramesh Keshavaraj

U.S. PTO Customer No. 25280

Case No.: 2102REI

CONCLUSION

It is believed that all of the claims are in condition for allowance and Applicant respectfully submit that the claims are in condition for allowance, and a notice to that effect is earnestly solicited. Should the Examiner find that any issues remain outstanding following consideration of this Response, she is invited to telephone the undersigned in the interest of resolving such matters in an expedient manner.

Respectfully submitted,

Sara M. Current Reg. No. 38,057

Phone No.: 864-503-1596

ia Munt

Milliken & Company 920 Milliken Road, M-495 Spartanburg, SC 29303